DEPARTMENT OF ENVIRONMENTAL CONSERVATION AIR QUALITY CONTROL CONSTRUCTION PERMIT

Permit No.: 079CP02 Date: Proposed – December 29, 2004

The Department of Environmental Conservation (Department), under the authority of AS 46.03, AS 46.14, AS 46.40, 6 AAC 50, 18 AAC 15, and 18 AAC 50.315, issues an Air Quality Control Construction Permit to the Permittee listed below.

Operator and Permittee: Alyeska Pipeline Service Company

900 E. Benson Blvd. Anchorage, AK 99508

Owner: Owners of the Trans-Alaska Pipeline System

Stationary Source: Trans-Alaska Pipeline System Pump Station 9

Location: Latitude: 63° 55' 53" North; Longitude 145° 45' 59" West

Physical Address: Section 27, T11S, R10E, Umiat Meridian, Alaska

Permit Contact: Don Mark Anthony (907) 450-7652

The Department authorizes the Permittee to install three reciprocating internal combustion engines (RICE) at Pump Station 9 as part of the **Strategic Recongifuration Project**.

This permit satisfies the obligation of the Permittee to obtain a construction permit as set out in AS 46.14.130. As required by AS 46.14.120, the Permittee shall comply with the terms and conditions of this construction permit.

This stationary source is classified under 18 AAC 50.300(c)(1). The project is a modification classified under 18 AAC 50.300(h)(2).

John F. Kuterbach, Manager Air Permits Program

Table of Contents

Section 1	Permit Terms and Conditions	∠
Emissi	ion Unit Inventory and Description	∠
Ambie	ent Air Quality Protection Requirements	6
Owner	Requested Limits to Avoid Project Classification as a PSD-Major Modification	7
State I	Emission Standards	7
Section 2	Permit Documentation	C

Abbreviations/Acronyms

AAC	Alaska Administrative Code
ADEC	Alaska Department of Environmental Conservation
	Alyeska Pipeline Service Company
	Alaska Statutes
ASTM	American Society of Testing and Materials
	Continuous Emission Monitoring System
C.F.R	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
	Dry Low Emissions
	Environmental Management System
EPA	Environmental Protection Agency
	Higher heating value
	Maximum Achievable Control Technology
	monitoring, recordkeeping, and reporting
	Not Applicable
	North American Industry Classification System
	National Emission Standards for Hazardous Air Pollutants
NSPS	New Source Performance Standards
PS	Performance specification
	Pump Station 9
	Prevention of Significant Deterioration
	Standard Industrial Classification
	Serial Number
	To Be Determined
Units and Me	asures
bhp	brake horsepower or boiler horsepower ¹
bhp gr./dscf	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)
bhp gr./dscf dscf	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic foot
bhp gr./dscf dscf gph	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)
bhp gr./dscf dscf gph kW	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hour
bhp gr./dscf dscf gph kW kW-e	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hourkiloWatts
bhpgr./dscfdscfgphkWkW-e	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hourkiloWattskiloWatts electric ²
bhpgr./dscfdscfgphkWkW-emmBtuppm	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hourkiloWattskiloWatts electric ² million British Thermal Units
bhpgr./dscfgr./dscfgphkWkW-eppmppm	brake horsepower or boiler horsepower grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric ² million British Thermal Units parts per million
bhp	brake horsepower or boiler horsepower ¹ grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hourkiloWattskiloWatts electric ² million British Thermal Unitsparts per millionparts per million by volume
bhp	brake horsepower or boiler horsepower grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric² million British Thermal Units parts per million parts per million by volume tons per hour
bhp	brake horsepower or boiler horsepower grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric² million British Thermal Units parts per million parts per million by volume tons per hour tons per year
bhp	brake horsepower or boiler horsepower grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric² million British Thermal Units parts per million parts per million by volume tons per hour tons per year
bhp	brake horsepower or boiler horsepower 1grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hourkiloWattskiloWatts electric2million British Thermal Unitsparts per millionparts per million by volumetons per hourtons per yearweight percent
bhp	brake horsepower or boiler horsepower 1grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hourkiloWattskiloWatts electric²million British Thermal Unitsparts per millionparts per million by volumetons per hourtons per yearweight percentCarbon MonoxideHazardous Air Pollutants
bhp	brake horsepower or boiler horsepower grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric² million British Thermal Units parts per million parts per million by volume tons per hour tons per year weight percent Carbon Monoxide Hazardous Air Pollutants Hydrogen Sulfide
bhp	brake horsepower or boiler horsepower 1grains per dry standard cubic feet (1 pound = 7,000 grains)dry standard cubic footgallons per hourkiloWattskiloWatts electric²million British Thermal Unitsparts per millionparts per million by volumetons per hourtons per yearweight percentCarbon MonoxideHazardous Air Pollutants
bhp	brake horsepower or boiler horsepower 1 grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric² million British Thermal Units parts per million parts per million by volume tons per hour tons per year weight percent Carbon Monoxide Hazardous Air Pollutants Hydrogen Sulfide Oxides of Nitrogen
bhp	brake horsepower or boiler horsepower 1 grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric² million British Thermal Units parts per million parts per million by volume tons per hour tons per year weight percent Carbon Monoxide Hazardous Air Pollutants Hydrogen Sulfide Oxides of Nitrogen Nitrogen Dioxide
bhp	
bhp	brake horsepower or boiler horsepower 1 grains per dry standard cubic feet (1 pound = 7,000 grains) dry standard cubic foot gallons per hour kiloWatts kiloWatts electric² million British Thermal Units parts per million parts per million tons per hour tons per year weight percent Carbon Monoxide Hazardous Air Pollutants Hydrogen Sulfide Oxides of Nitrogen Nitrogen Dioxide Nitric Oxide

¹ For boilers: One boiler horsepower = 33,472 Btu-fuel per horsepower-hour divided by the boiler's efficiency. For engines: approximately 7,000 Btu-fuel per brake horsepower-hour is required for an average diesel internal combustion engine.

² kW-e refers to rated generator electrical output rather than engine output

Section 1 Permit Terms and Conditions

Emission Unit Inventory and Description

1. Authorization. The Permittee may install Emission Units 10, 11, and 12 listed in Table 1, or alternative units as described in condition 1.1, at this stationary source in accordance with the terms and condition of this permit and the original construction permit application and subsequent submittals listed in Section 2. Upon installation of any Emission Unit 10 through 12, the Permittee shall limit hours of operation of existing Unit No. 8 as indicated in condition 2.

No.	Туре	Make/Model	Fuel	Rating/Size	Action
8	Firewater Pump	Cummins N-855F	Distillate Oil	400 kW	Modify
10	Reciprocating Internal Combustion Engine	Caterpillar 3516B	Diesel	2,250 kW	Install
11	Reciprocating Internal Combustion Engine	Caterpillar 3516B	Diesel	2,250 kW	Install
12	Reciprocating Internal Combustion Engine	To Be Determined (TBD)	Diesel	65 kW-e	Install

Table 1 - Construction Permit Emission Unit Inventory^a

Table Notes:

- 1.1 If the Permittee elects to install an alternative to the units listed in Table 1, the alternative unit shall be of equal or lesser rating/size than the unit it is replacing in Table 1. At least 30 days before installation of the alternative unit, submit to the Department's Fairbanks office a demonstration that the maximum emission rates of NO_X, CO, PM-10, and VOC for the alternative unit are equal to or less than those from the unit it is replacing.
- 1.2 At least five days before initial startup³ of Emission Units 10 through 12 or alternative units, submit the following to the Department's Fairbanks office:
 - a. vendor specification sheets that identify the unit type, make and model (including model number), serial number, and rating/size; and
 - b. the installation date and estimated date of startup.

Page 4 of 9

Except as noted elsewhere in this permit, the information in this table is for identification purposes only.

³ Initial Startup means when the emission unit is first fired.

- 1.3 Unless an extension is granted by the Department in writing as indicated in condition 1.4, decommission⁴ existing Emission Units 1 through 7 listed in Table 1 of initial Operating Permit No. 079TVP01 within 270 calendar days after actual initial startup of any Emission Unit 10 through 12 or alternative unit. During the 270 day "startup period":
 - a. do not operate any of the new Emission Units 10 through 12, or alternative units, concurrently with Emission Units 1 through 7, except during start-up, shut-down, or system performance testing of new Emission Units 10 through 12;
 - b. for any time any new Emission Unit 10 through 12 or alternative unit is operated, record the emission unit number, startup time and date, shutdown time and date, duration of operation, and whether any existing Emission Unit 1 through 7 operated concurrently; and
 - c. if an existing Emission Unit 1 through 7 operates concurrently with new Emission Units 10 through 12 or alternative unit, include the operational mode of each new Emission Unit 10 through 12 or alternative unit with the information recorded in condition 1.3b, and if the operational mode is other than startup, shutdown, or performance test, report as a permit deviation under condition 46 of initial Operating Permit No. 079TVP01.
- 1.4 The Department may allow an extension of the "startup period" for due cause. Submit a request for an extension in writing to the Department's Fairbanks office within 240 days of initial startup of any Emission Unit 10 through 12 or alternative unit. Include a description of the reason for the extension. The Department will grant an extension of up to 30 days if the Department finds due cause exists.
- 1.5 Include with the next operating report required by condition 48 of initial Operating Permit No. 079TVP01:
 - a. the actual initial startup dates for each Emission Unit 10 through 12 or alternative units;
 - b. the decommissioning dates for each Emission Unit 1 through 7; and
 - c. copies of the notifications and records required by conditions 1.1, 1.2, and 1.3.

Page 5 of 9

⁴ Decommission means the fuel systems and generator electrical leads have been disconnected.

Ambient Air Quality Protection Requirements

2. Operational Limits (NO_X, SO₂, PM-10). The Permittee shall restrict operating hours of Emission Units 8, 10, 11, and 12 to no more than the limits listed in Table 2 to protect ambient air quality.

Table 2 – Operating Hour Limits^a

Emission Unit No.	Limit in hours		
8	10 hours per calendar day		
10 and 11, combined	11,200 per 12 consecutive months		
12	300 per 12 consecutive months		

- 2.1 Using an hour totalizer accurate to within two percent, monitor and record total hours of operation for
 - a. Unit 8 on a daily basis;
 - b. Units 10 and 11, combined, on a monthly basis; and
 - c. Unit 12 on a monthly basis.
- 2.2 By the 15th of each month, add monthly total for Units 10 and 11 combined, and Unit 12 individually, to previous 11 months to get 12 consecutive month total.
- 2.3 Report according to condition 46 of initial Operating Permit No. 079TVP01 if any daily or 12 consecutive month total exceeds a limit in Table 2.
- 2.4 Include copies of records required under conditions 2.1 and 2.2 with the operating report for that period required under condition 48 of initial Operating Permit No. 079TVP01.
- **3. Fuel Sulfur** (**SO**₂). The Permittee shall limit the diesel fuel sulfur content for Emission Units 10, 11, and 12 to no more than 0.24 percent by weight.
 - 3.1 Monitor according to condition 5.2a, 5.3b, and 5.3c of initial Operating Permit No. 079TVP01.
 - 3.2 Report according to condition 46 of initial Operating Permit No. 079TVP01, any time the diesel fuel sulfur content exceeds 0.24 percent by weight.

Owner Requested Limits to Avoid Project Classification as a PSD-Major Modification

- 4. Oxides of Nitrogen (NO_X) Limit. The Permittee shall
 - comply with operating hour limits listed in Table 2; a.
 - b. limit the emissions of NO_X from Emission Units 10 and 11 to no more than 396.5 tons in any 12 consecutive months; and
 - By the 15th of each month, calculate and record the NO_X emissions for the previous 4.1 month and the total NO_x emissions for the previous 12 consecutive months for Emission Units 10 and 11, combined, using Equation 1.

Equation 1
$$NO_X = \frac{ER_{NOX} \times hrs}{0.87 \times 2,000}$$

NO_X emissions in tons per month; NO_X Where:

 $ER_{NOX} = hrs =$ 61.6 lb NO_X per hour⁵

Unit 10 and 11 combined operating hours from

condition 2.1b; and

humidity correction factor at PS 96. 0.87 =

- 4.2 Report as excess emissions under condition 46 of initial Operating Permit 079TVP01 if the 12 consecutive month total NO_X emissions calculated under condition 4.1 exceed 396.5 tons.
- 4.3 Report under condition 48 of initial Operating Permit No. 079TVP01 the monthly and 12 consecutive month total NO_X emissions for Emission Units 10 and 11.

State Emission Standards

- 5. **Visible Emissions.** The Permittee shall not cause or allow visible emissions, excluding condensed water vapor, emitted from Emission Units 10 through 12 to reduce visibility through the exhaust effluent by any of the following:
 - more than 20 percent for a total of more than three minutes in any one hour; a.
 - more than 20 percent averaged over any six consecutive minutes. b.
- 6. **Particulate Matter (PM).** The Permittee shall not cause or allow PM emissions from any Emission Unit 10 through 12 to exceed 0.05 grains per dry standard cubic foot (gr/dscf) of exhaust gas corrected to standard conditions and averaged over three hours.

⁵ Vendor data, APSC construction permit application for the strategic reconfiguration of PS 9, September 2004, page 5 of Appendix B.

APSC construction permit application for the strategic reconfiguration of PS 9, September 2004, page 2-19.

7. Sulfur Compound Emissions. The Permittee shall not cause or allow sulfur compound emission, expressed as SO₂, from any Emission Unit 10 through 12 to exceed 500 ppm averaged over three hours.

Section 2 Permit Documentation

September 8, 2004 Letter from Gregory T. Jones, APSC, to Jim Baumgartner, ADEC, with an application for an Air Quality Control Construction Permit.

November 3, 2004 Letter from Pete Miller, The RETEC Group, to Alan Schuler, ADEC, ambient modeling supplement.